

## HSE profile and Green Building contribution Hilti Firestop Cushion CP 651N, CFS-CU

**LEED** and **BREEAM** are third-party certification programs which provide a benchmark for the design, construction and operation of high-performance green buildings. Both promote a whole-building approach to sustainability and evaluate it by scoring points based on a set of criteria. Individual products cannot be certified under LEED or BREEAM but they can contribute to criterion compliance (prerequisites or credits).

The following information shows the areas where Hilti Firestop Cushions can potentially contribute, as well as the maximum number of points that can be achieved by accomplishing each criteria and state the required values and explanations for the building certification process.

**Hilti Firestop Cushion** is a ready-to-use tear-resistant and dust-free firestop pillow. It is easy to use and reusable. It is intumescent and non-conductive.







		LEED		BREEAM	
Sustainable sites management		Criteria (Up to # points) & Evaluation			
Construction site waste	No waste or dust generation during installation and repenetration	SS Prerequisite 1	**	Wst 1 (3) Man 3d (4 for Man 3)	**
Life cycle assesment, Product Carbon Footprint	Under evaluation	SS Credit 5.2 (1)	<b>☆☆</b> ☆	Man 3a (4 for Man 3) Mat 1 (4)	<b>☆☆</b> ☆
Water consumption	No water demand during installation and repenetration	WE Credit 2 (2)	$^{\uparrow}$	Man 3c (4 for Man 3)	$\stackrel{\wedge}{\simeq} \stackrel{\wedge}{\simeq} \stackrel{\wedge}{\simeq}$
Water pollution	no waste water generation during installation and		***	Man 3e (4 for Man 3)	***
Application	No electric tool needed for installation and repenetration	-		-	

**Energy Optimization, Atmosphere and Pollution** 

Air tightness*	Not determined	EA Prerequisite 2	<b>☆</b> ☆☆	Ene 1 (15) Ene 6 (1)	<b>☆</b> ☆☆
Thermal insulation*	Not determined	EA Credit 1 (1-19) IEQ Credit 7.1 (1)	<b>☆</b> ☆☆	Ene 1 (15) Mat 6 (2)	<b>☆</b> ☆☆
Ozone Depletion Potential	Under evaluation	EA Prerequisite 3	<b>☆☆☆</b>	IC (1)	$\bigstar \bigstar \diamondsuit$

## **Materials and Resources**

Reusability	It is fully reusable	MR Credit 1.1 (1-3) MR Credit 1.2 (1)	***	Wst 1 (3)	***
TProduct recycling	The product cannot be recycled or salvaged but the packaging can be totally recycled or salvaged	MR Credit 2 (1-2)	***	Wst 1 (3)	\$\$\$
Recycled content	No, since firestop products require the traceability of their raw materials to guarantee uniform and constant product performance and quality.	MR Credit 4 (1-2)	\$\$\$		######################################
	The packaging is partially manufatured with recycled material		$\stackrel{\wedge}{\mathbf{A}} \stackrel{\wedge}{\mathbf{A}} \stackrel{\wedge}{\mathbf{A}}$	Mat 5 (3)	<b>☆☆</b> ☆
Product origin	Raw materials origin: PR of China	MR Credit 5 (1-2)	<b>☆</b> ☆☆		<b>☆☆☆</b>
	Manufacturing location: PR of China		<b>☆</b> ☆☆		<b>☆☆☆</b>
Rapidly Renewable Materials	Raw materials are not rapidly renewable	MR Credit 6 (1)	\$ \$ \$ \$		

Indoor Environmental Quality, Health and Wellbeing

indoor Environmental Quality, Health and Wellbeing					
IAQ (Indoor Air Quality) Management	No dangerous good or labelling needed and no content of carcinogens	IEQ Credit 3.1 (1) IEQ Credit 3.2 (1)		-	
	Halogen Free Flame Retardants	ied Credit 3.2 (1)	$^{\uparrow}$	?	
Low-Emitting Materials Volatile Organic Compounds	VOC acc to LEED 2009 / EPA #24: 6.6 g/l - see certificate dated Sept 21, 2009	IEQ Credit 4.1 (1) IEQ Credit 4.2 (1)	***	Hea 9 (1)	***
Soundproofing	Rw** = 50 dB and STC** = 49 (refer to test report 164 32099/Z01-Z04 dated Oct. 9, 2006). Protection to the sound passage and noise reduction.	-		Hea 13 (1)	***

Product highly contributes to Green Building certification under this clause

Product contributes to Green Building certification under this clause

Not applicable for this product or dependent on each situation and so not possible to evaluate in general terms
Product makes no contribution to Green Building certification under this clause

Issued June 2013

BU Chemicals, CETsp&CMT

<sup>\*</sup> Lower heating and cooling costs \*\* Sound reduction Index



## The sustainability of sites is improved with Hilti Firestop Cushions by supporting LEED, BREEAM and the following extra properties and highly important characteristics of a building, as well as, preventing effectively from the spread of a fire:



The spread of fire in a building is probably the worst scenario owners or occupants can imagine. When it comes to effectively minimizing the effects of fire, the interplay of a variety of systems and elements is required. Active fire protection – including components such as fire alarms and fire extinguishers – is taken into account in many buildings. On the other hand, often less emphasis is placed on measures, which help to contain fire at its point of origin and prevent the spread of fire and smoke effectively. This should ideally be designed already in the planning phase. Components of passive fire protection create effective barriers against the passage of fire, smoke and toxic gases through openings in walls or floors, resulting from through-penetrations of cables and pipes, from construction joints or other damages.



Sound insulation is of great importance to the health and well-being of the occupants of a building. Hilti firestop products are tested for this purpose and individually tailored to the requirements of the installation and building structure. Hilti Firestop Cushions, tested in accordance with ISO 140-3, 20140-10 and 717-1 standard, allow compliance with the applicable sound insulation specifications for fireproofed penetrations through walls and floors, and joints between building components.



Mold in a building can attack and weaken many types of building materials and fungus, caused by moisture and humidity, can be seriously detrimental to the health of building users. Measures to successfully prevent the formation of mold and mildew in a building must be taken at the planning stage. Hilti Firestop Cushions are manufactured with materials that provide no nutrition for fungi and tested in accordance with ISO 846 and ASTM G21, to ensure that functionality is not compromised.

All the packagings and cans used by Hilti can be recycled. Hilti Firestop Cushions are ready-to-use, so no waste is generated on the jobsite during the construction phase, and they are considered household waste at the end of the life of the building. Please consider your national law regarding the disposal of the Firestop Cushion and contact your local Hilti partner for further information.



If you need additional information or documentation on a certain HSE issue, please do not hesitate to contact your local Hilti partner - we are happy to provide you with additional information required to make your green building project a success.



Hilti Firestop Cushions have been registered in the Swedish database BASTA. BASTA registration means that we confirm that this product meets agreed properties criteria regarding properties that are harmful to the environment and health. See www.bastaonline.se.

Issued June 2013

BU Chemicals, CETsp&CMT