

Avvitatore a impulsi a batteria, inserti percussione e bits
per tasselli ancoranti HRD-C e viti ad ancoraggio HUS-S, HUS-P, HUS, HUS-H, HUS-I, HUS-A

Per praticare fori per tasselli
Ø 6 mm in muratura



TKI-S 6/20
(220686)



TKI-S 6/35
(220687)



HRD-C 8



S-B TX25 50/2" IMP (5)
(2039131)



S-B TX25 IMP
(2039121)



S-BH
(2039216)



HUS-S 6



HUS3-P 6



S-B TX30 50/2" IMP (5)
(2039132)



S-SY TX130 S
(2039157)



S-BH
(2039216)



HUS 6



S-B TX40 50/2" IMP (5)
(2039133)




S-B TX40 25/1" IMP
(2039123)



S-BH
(2039216)



HUS3-H 6



S-NS 13 C 90/3 1/2
(2039251)



HUS3-I 6



SI-S 1/2"-13 S
(2070371)



HUS3-A 6



SI-S 1/2"-13 L
lungo e a parete sottile per binario MM
(2070402)



SID 4-22
SID 6-22



SIW 4AT-22



Panoramica applicazioni – viti

Filetti ISO metrici	M5	M6	M8	M10	M12	M14	M16	M18	M20	M22	M24
Larghezza chiave [mm]	8	10	13	17	19	22	24	27	30	32	36
SIW 2-A12, SID 2-A12	■	■	■	■	■						
SIW 4AT-22, SID 4/6-22			■	■	■						
SIW 6-22					■	■	■	■	■		
SIW 8-22							■	■	■	■	■

Panoramica applicazioni – tasselli

	HUS				HRD		
Diametro [mm]	6	8	10	14	8	10	14
Larghezza chiave [mm]	T30/SW13	T45/SW13	T45/SW15	SW21	T30	T40/SW13	T50/SW17
SIW 2-A12, SID 2-A12	■				■		
SIW 4AT-22, SID 4/6-22	■	■			■		
SIW 6-22		■	■		■	■	■
SIW 8-22			■	■	■	■	■