





P8

Inspection Document  
EN 10204  
Prüfbescheinigung

HILTI (CHINA) LTD.  
Yongping Road, South,  
Zhanjiang, Guangdong, PRC

Document No. Dokument Nr.

P8\_2.2\_150

Item-Nr.	Product designation	Customer ref. -Nr.	Batch-Nr.	Quantity
Sach-Nr.	Produktbezeichnung	Kunden Ref. Nr.	Charge/Los Nr.	Menge
Code art.	Référence produit	No. ref. de client	Commande No.	Quantité
409551	Anchor rod HIT-V-F M10x95			

Item designation	Anchor rod	Rod	Nut	Washer		
Sachbezeichnung	HIT-V-F	螺杆	螺母	垫片		
Reference composant	M10x95					

## Inspection values/Prüfergebnisse

Chemical composition		set value	actual value	set value	actual value	set value	actual value	set value	actual value	set value	actual value
Chem. Zusammensetzung											
C %		0.00-0.55	0.19	0.00-0.58	0.08						
Si %											
Mn %				min. 0.30	0.42						
P %		0.000-0.050	0.017	0.000-0.060	0.011						
S %		0.000-0.060	0.010	0.000-0.150	0.008						
Cr %											
Mo %											
Ni %											
Cu %											
B %											
Al %											
N %											
Pb %											
Mech. properties											
Mechanische Eigensch. / Mecan. prop.											
N											
V											
F <sub>p</sub>				46	46						
HV						140-250	147-170				
HRC											
A		min. 10	15-17								
Z											
R <sub>p0.2</sub>		min. 420	466-498								
R <sub>m</sub>		min. 520	613-624								
Layer thickness/Schichtdicke											
Epaisseur de couche extérieure											
d (Zn)		min. 40	61-85	min. 40	46-65	min. 40	44-67				
N	kN	Tension load / Bruchlast Zug / charge de tension				Z	%	Reduction of area / Einschnürung / contraction			
V	kN	Shear load / Querlast / charge de cisaillement				R <sub>p0.2</sub>	N/mm <sup>2</sup>	Yield strength / Streckgrenze / limite d'élasticité			
F <sub>p</sub>	N	Proof load / Prüfkraft / charge limite				R <sub>m</sub>	N/mm <sup>2</sup>	Ultimate tensile strength / Zugfestigkeit / résistance à la			
HV	-	Vickers hardness / Härte Vickers / durezza Vickers				d (Zn)	µm	Mean zinc thickness/ mittlere Schicht-dicke Zn / epaisseur			
A	%	Elongation after fracture / Bruch-dehnung / elongation après fracture									